



## Performance Data 50Hz

MODEL (50Hz)		P2		Delivery									
				n≈2850 1/min									
				m³/h	0	1.8	3.6	5.4	7.2	9.0	10.8	12.6	14.4
1 - 220-240V	3 - 380 - 415V	kW	HP	l/min	0	30	60	90	120	150	180	210	240
4SDM10/5	4SD10/5	0.75	1	HEAD (m)	31	30	28	27	25	22	18	13	7
4SDM10/6	4SD10/6	1.1	1.5		37	36	34	32	30	26	22	15	9
4SDM10/7	4SDM10/7	1.1	1.5		43	42	39	38	35	31	25	18	10
4SDM10/8	4SD10/8	1.5	2		49	48	45	43	40	35	29	21	12
4SDM10/10	4SD10/10	1.5	2		62	59	56	54	50	44	36	26	14
4SDM10/12	4SD10/12	2.2	3		74	71	68	64	60	53	43	31	17
4SDM10/14	4SD10/14	2.2	3		86	83	79	75	70	62	51	36	20
-	4SD10/16	3	4		99	95	90	86	80	71	58	41	23
-	4SD10/18	3	4		111	107	101	96	90	79	65	46	26
-	4SD10/20	4	5.5		123	119	113	107	100	88	72	52	29
-	4SD10/22	4	5.5		136	131	124	118	110	97	79	57	32
-	4SD10/25	5.5	7.5		154	149	141	134	125	110	90	65	36
-	4SD10/28	5.5	7.5		176	166	158	150	140	124	101	72	40
-	4SD10/32	7.5	10		197	190	180	172	160	141	116	83	46
-	4SD10/36	7.5	10	222	214	203	193	180	159	130	93	52	