



Performance Data 50Hz

MODEL (50Hz)		P2		Delivery $n \approx 2850$ 1/min								
1 - 220-240V	3 - 380 - 415V	kW	HP	m ³ /h	0	3	6	9	12	15	18	21
				l/min	0	50	100	150	200	250	300	350
4SDM16/4	4SD16/4	1.1	1.5	HEAD (m)	24	23	22	20	18	15	12	9
4SDM16/5	4SD16/5	1.5	2		30	29	28	25	22	19	15	11
4SDM16/6	4SD16/6	1.5	2		36	35	33	30	26	22	18	13
4SDM16/8	4SD16/8	2.2	3		47	46	44	40	35	30	24	17
4SDM19/9	4SD19/9	2.2	3		53	52	50	45	40	33	27	19
-	4SD16/11	3	4		65	64	61	55	48	41	33	24
-	4SD16/12	3	4		71	70	66	60	53	45	36	26
-	4SD16/14	4	5.5		83	81	77	70	62	52	42	30
-	4SD16/16	4	5.5		95	93	88	80	70	60	48	35
-	4SD16/18	5.5	7.5		107	104	99	90	79	67	54	39
-	4SD16/20	5.5	7.5		118	116	110	100	88	74	60	43
-	4SD16/23	7.5	10		136	133	127	115	101	86	69	50
-	4SD16/25	7.5	10		148	145	138	125	110	93	75	54