



Performance Data 50Hz

MODEL (50Hz)		P2		Delivery									
				n≈2850 1/min									
1 - 220-240V	3 - 380 - 415V	kW	HP	m³/h	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8
				l/min	0	10	20	30	40	50	60	70	80
4SDM3/7	4SD3/7	0.37	0.5	HEAD (m)	50	49	47	45	41	35	28	20	10
4SDM3/10	4SD3/10	0.55	0.75		72	70	68	64	58	50	40	29	15
4SDM3/11	4SD3/11	0.75	1		79	77	75	70	64	56	45	32	16
4SDM3/13	4SD3/13	0.75	1		93	91	88	83	76	66	53	38	19
4SDM3/15	4SD3/15	1.1	1.5		108	105	102	96	88	76	61	43	22
4SDM3/18	4SD3/18	1.1	1.5		129	126	122	115	105	91	73	52	27
4SDM3/20	4SD3/20	1.5	2		144	140	135	128	117	101	81	58	30
4SDM3/22	4SD3/22	1.5	2		158	154	149	141	128	111	89	64	33
4SDM3/26	4SD3/26	2.2	3		187	182	176	166	152	131	105	75	39
-	4SD3/30	2.2	3		215	210	203	192	175	151	121	87	45
-	4SD3/35	3	4		251	245	237	224	204	177	142	101	52
-	4SD3/40	3	4		287	280	271	255	234	202	162	115	60
-	4SD3/45	4	5.5		323	315	305	287	263	227	182	130	67
-	4SD3/50	4	5.5		359	350	339	319	292	252	202	144	75
-	4SD3/56	5.5	7.5		402	392	379	358	327	283	227	162	84
-	4SD3/62	5.5	7.5		445	434	420	396	362	313	251	179	93