



Performance Data 50Hz

MODEL (50Hz)		P2		Delivery n≈2850 1/min									
1 - 220-240V	3 - 380 - 415V	kW	HP	m³/h		0	1.2	2.4	3.6	4.8	6.0	7.2	8.4
				l/min		0	20	40	60	80	100	120	140
4SDM6/5	4SD6/5	0.37	0.5	HEAD (m)	36	34	33	31	28	24	19	12	
4SDM6/6	4SD6/6	0.55	0.75		43	41	39	37	34	29	23	15	
4SDM6/7	4SD6/7	0.75	1		51	47	46	44	40	33	26	17	
4SDM6/8	4SD6/8	0.75	1		58	54	52	50	45	38	30	20	
4SDM6/9	4SD6/9	1.1	1.5		65	61	59	56	51	43	34	22	
4SDM6/11	4SD6/11	1.1	1.5		80	74	72	69	62	52	41	27	
4SDM6/12	4SD6/12	1.5	2		87	81	79	75	68	57	45	29	
4SDM6/14	4SD6/12	1.5	2		101	95	92	87	79	67	53	34	
4SDM6/17	4SD6/17	2.2	3		123	115	111	106	96	81	64	42	
4SDM6/20	4SD6/20	2.2	3		145	135	131	125	113	95	75	49	
-	4SD6/23	3	4		166	156	151	143	130	110	87	56	
-	4SD6/26	3	4		188	176	171	162	147	124	98	63	
-	4SD6/30	4	5.5		217	203	197	187	170	143	113	73	
-	4SD6/34	4	5.5		246	230	223	212	193	162	128	83	
-	4SD6/38	5.5	7.5	275	257	249	237	216	181	143	93		
-	4SD6/42	5.5	7.5	304	284	275	262	238	200	158	103		
-	4SD6/47	7.5	10	340	318	308	293	267	224	177	115		
-	4SD6/52	7.5	10	376	352	341	324	295	248	196	127		