



MODEL NAME		RATING		DISCHARGE										
Three-Phase	Stage	kW	HP	l/min m ³ /h	0	167	335	500	585	670	750	835	917	1000
					0	10.0	20.1	30.0	35.1	40.2	45.0	50.1	55.0	60.0
VP48A-05	5	7.50	10.00	Head (m)	68	64	60	55	52	48	44	39	33	27
VP48A-06	6	9.20	12.30		81	77	72	66	62	58	53	47	40	32
VP48A-07	7	11.00	15.00		94	90	84	77	73	68	62	55	47	37
VP48A-08	8	13.00	17.50		108	103	96	88	83	77	71	63	53	43
VP48A-09	9	15.00	17.50		122	116	108	99	93	87	79	70	60	48
VP48A-10	10	15.00	17.50		135	129	120	110	104	97	88	78	67	53
VP48A-11	11	18.50	25.00		148	142	132	121	114	106	97	86	73	59
VP48A-12	12	18.50	25.00		162	155	144	132	124	116	106	94	80	64
VP48A-13	13	22.00	30.00		176	168	157	143	135	126	115	102	87	69
VP48A-14	14	22.00	30.00		189	181	169	154	145	135	124	110	93	75
VP48A-15	15	22.00	30.00		202	194	181	165	156	145	132	117	100	80
VP48A-16	16	26.00	35.00		216	206	193	176	166	155	141	125	107	85
VP48A-17	17	26.00	35.00		230	219	205	187	176	164	150	133	113	91
VP48A-18	18	30.00	40.00		243	232	217	198	187	174	159	141	120	96
VP48A-19	19	30.00	40.00		256	245	229	209	197	184	168	149	127	101
VP48A-20	20	30.00	40.00		270	258	241	220	207	193	177	157	133	107
VP48A-21	21	37.00	50.00		284	271	253	231	218	203	185	164	140	112
VP48A-22	22	37.00	50.00		297	284	265	242	228	213	194	172	147	117
VP48A-23	23	37.00	50.00		310	297	277	253	239	222	203	180	153	123
VP48A-24	24	37.00	50.00		324	310	289	264	249	232	212	188	160	128

MODEL NAME	SPECIFICATIONS			
	D (mm)	L (mm)	Pump Weight (kg)	Total Weight [incl packaging] (kg)
VP48A-05	147	848	20	24
VP48A-06	147	961	18	23
VP48A-07	147	1074	20	25
VP48A-08	147	1187	22	28
VP48A-09	147	1300	24	29
VP48A-10	147	1413	26	34
VP48A-11	147	1526	28	36
VP48A-12	147	1639	32	42
VP48A-13	147	1752	34	44
VP48A-14	147	1865	36	46
VP48A-15	147	1987	38	48
VP48A-16	147	2091	40	50
VP48A-17	147	2204	42	52
VP48A-18	147	2317	44	54
VP48A-19	147	2430	46	56
VP48A-20	147	2543	48	58
VP48A-21	147	2656	55	60
VP48A-22	147	2769	57	62
VP48A-23	147	2882	60	65
VP48A-24	147	2995	62	67

